

Amendments to the Claims

Entry of the following amendments to the claims is respectfully requested.

1. (Currently amended) A positioning device for precisely positioning a microtiter plate on a support, wherein the positioning device comprises: a) a support having a first axis and a second axis, b) a microtiter plate, and c) at least a first alignment member that protrudes from the support along the first axis, wherein the alignment member is in contact with an inner wall at an edge of a well area of the microtiter plate and the microtiter plate is positioned along the first axis with an error tolerance of 0.066 millimeter or less.

2. (Previously presented) The positioning device of claim 1, wherein the device comprises two or more alignment members that protrude from the support along the first axis and are in contact with a single inner wall of the microtiter plate when the microtiter plate is in the desired position on the support.

3. (Previously presented) The positioning device of claim 1, wherein the positioning device further comprises at least a second alignment member that protrudes from the support along the second axis and is in contact with a second wall of the microtiter plate when the microtiter plate is in the desired position along the second axis on the support.

4. (Original) The positioning device of claim 3, wherein the second wall of the microtiter plate is an inner wall.

5. (Original) The positioning device of claim 4, wherein the first inner wall and the second inner wall form a right angle.

6. (Previously presented) The positioning device of claim 4, wherein two or more alignment members are positioned on the support along the first axis such that the alignment members are in contact with the first inner wall of the microtiter plate, and at least a third alignment member is positioned on the support along the second axis such that the third

alignment member is in contact with the second inner wall, when the microtiter plate is in the desired position on the support.

7. (Original) The positioning device of claim 1, wherein one or more of the alignment members comprises a curved surface that contacts the inner wall of the microtiter plate.

8. (Original) The positioning device of claim 7, wherein one or more of the alignment members comprises a locating pin.

9. (Previously presented) The positioning device of claim 1, which further comprises a pusher that is movably positioned on the support such that movement of the pusher towards the microtiter plate holds the first inner wall of the microtiter plate in contact with one or more of the alignment members.

10. (Previously presented) The positioning device of claim 9, wherein the positioning device comprises a second pusher that is movably positioned on the support such that when a microtiter plate is placed on the support, movement of the second pusher towards the microtiter plate can move the microtiter plate in a second direction to bring a second inner wall of the microtiter plate into contact with one or more of the alignment members.

11. (Previously presented) The positioning device of claim 10, wherein the device comprises two alignment members that protrude from the support along the first axis and are in contact with the first inner wall of a microtiter plate when the microtiter plate is in a desired position.

12. (Original) The positioning device of claim 1, wherein the positioning device comprises a retaining device which retains the microtiter plate in the desired position on the support.

13. (Original) The positioning device of claim 12, wherein the retaining device comprises a vacuum plate.

14. (Previously presented) A retaining device for retaining a microtiter plate in a desired position on a support, wherein the retaining device comprises a vacuum plate and a microtiter plate that is placed on the vacuum plate, wherein the vacuum plate comprises: a) a lip surface that is in contact with a bottom surface of an outer wall of the microtiter plate, b) an interior surface that is recessed relative to the lip surface, and c) a vacuum groove disposed between the interior surface and the lip surface, wherein when a vacuum is applied, the vacuum plate holds the microtiter plate in the desired position.

15. (Original) The retaining device of claim 14, wherein the vacuum plate is connected to a vacuum source.

16. (Canceled)

17. (Previously presented) The retaining device of claim 14, wherein the depth at which the interior surface is recessed is between 0.001 inches and 0.01 inches.

18. (Previously presented) The retaining device of claim 14, wherein a support matrix approximately as thick as the depth at which the interior surface is recessed is present on the interior surface to prevent distortion of the microtiter plate when a vacuum is applied.

19. (Original) The retaining device of claim 14, wherein the device comprises a vacuum-actuated switch that, when the microtiter plate forms an airtight seal with the vacuum plate, generates a signal that the microtiter plate is properly positioned.

20. (Original) The retaining device of claim 19, wherein the signal notifies a controller that the microtiter plate is ready for further processing.

21. (Currently amended) An object holder for precisely positioning a microtiter plate on a support, wherein the object holder comprises:

- a support having a first axis and a second axis;
- a microtiter plate that is placed on the support;
- a set of one or more first alignment members that protrude from the support along the first axis and are in contact with a first alignment surface of the microtiter plate;
- a set of one or more second alignment members that protrude from the support along the second axis and are positioned to be in contact with a second alignment surface of the microtiter plate when the microtiter plate is in a desired position on the support;
- a first pusher that is movably positioned on the support such that movement of the first pusher towards the microtiter plate holds the first alignment surface of the microtiter plate in contact with one or more of the first set of alignment members, thereby positioning the microtiter plate along the first axis with an error tolerance of 0.066 millimeter or less; and
- a second pusher that is movably positioned on the support such that when a microtiter plate is placed on the support, movement of the second pusher towards the microtiter plate moves the microtiter plate in a second direction so that the second alignment surface of the microtiter plate contacts one or more of the second set of alignment members, thereby positioning the microtiter plate along the second axis with an error tolerance of 0.066 millimeter or less; wherein

wherein the first pusher comprises a lever pivoting about a pivot point, and further wherein either or both of the first alignment surface and the second alignment surface is an inner wall at an edge of a well area of the microtiter plate.

22. (Previously presented) The object holder of claim 21, wherein the lever is operably attached to a spring which causes the pusher to apply a constant force to the object in order to hold the microtiter plate against the first set of alignment members.

23. (Previously presented) The object holder of claim 21, wherein the first pusher comprises a low friction contact point which contacts the microtiter plate, thus facilitating movement of the microtiter plate in the second direction by the second pusher.

24. (Original) The object holder of claim 23, wherein the low friction contact point is a roller.

25. (Canceled)

26. (Canceled)

27. (Previously presented) The object holder of claim 21, wherein the object holder comprises one or more sensors that detect the position of one or more of the pushers, thereby determining whether the microtiter plate is in a desired position.

28. (Previously presented) The object holder of claim 21, wherein the object holder comprises a controller that first directs the first pusher to hold the microtiter plate against the first set of alignment members, then directs the second pusher to move the object in a second direction, and subsequently directs a retaining device to be activated.

29. (Canceled)

30. (Canceled)

31. (Canceled)

32. (Canceled)

33. (Canceled)

34. (Canceled)

35. (Currently amended) An object holder for receiving and retaining a microtiter plate in a desired orientation, the microtiter plate having a first alignment surface and a second

alignment surface, either or both of which comprises an inner wall at an edge of a well area of the microtiter plate, the object holder comprising:

a microtiter plate;

a support fixture;

a retaining device on the fixture;

a first alignment member supported on the fixture that is in contact with the first alignment surface of the microtiter plate;

a second alignment member supported on the fixture and positioned to cooperate with the second alignment surface of the microtiter plate;

a first pusher supported on the fixture and having a relaxed position and a tensioned position, the first pusher arranged to cooperate with the microtiter plate to hold the first alignment surface of the object firmly against the first alignment member as the first pusher is moved from the relaxed position to the tensioned position, thereby positioning the microtiter plate in a desired position along a first axis with an error tolerance of 0.066 millimeter or less;

a second pusher supported on the fixture and having a relaxed position and a tensioned position, the second pusher arranged to cooperate with the microtiter plate to move the second alignment surface of the plate firmly against the second alignment member as the second pusher is moved from the relaxed position to the tensioned position, thereby positioning the microtiter plate in a desired position along a second axis with an error tolerance of 0.066 millimeter or less;

a controller operably connected to the retaining device, the first pusher, and the second pusher, and

wherein the controller directs the first pusher to its tensioned position, directs the second pusher to its tensioned position, and directs the clamp to be activated, so that the microtiter plate is retained in the object holder in a desired orientation.

36. (Canceled)

37. (Previously presented) The object holder according to claim 35, wherein the retaining device is a vacuum plate connected to a vacuum source.

38. (Original) The object holder according to claim 37, wherein the object is a microtiter plate that has a well area, and the vacuum plate cooperates with a bottom of the well area to securely hold the plate.

39. (Currently amended) A method of receiving and retaining a microtiter plate in a desired orientation, the microtiter plate having a first alignment surface and a second alignment surface, wherein either or both of the first alignment surface and the second alignment surface is an inner wall at an edge of a well area of the microtiter plate, the method comprising:

placing the first alignment surface of the microtiter plate loosely adjacent a first alignment member, and placing the second alignment surface of the microtiter plate loosely adjacent a second alignment member;

moving a first pusher against the microtiter plate so that the first alignment surface is held firmly against the first alignment member, thereby positioning the microtiter plate in a desired position along a first axis with an error tolerance of 0.066 millimeter or less; and

moving a second pusher against the microtiter plate so that the second alignment surface is held firmly against the second alignment member, thereby positioning the microtiter plate in a desired position along a second axis with an error tolerance of 0.066 millimeter or less.

40. (Original) The method of claim 39, wherein the method further comprises verifying that either or both of the first pusher and the second pusher are properly positioned to hold the object against the alignment members.

41. (Original) The method of claim 39, wherein the method further comprises activating a retention device that holds the object in the desired orientation.

42. (Original) A software program which operates on a controller, wherein the software directs the controller to implement the method of claim 39.